










ID	Items and notes
1	MultiPlus(-II) or Quattro(-II) inverter/charger for 12, 24 or 48V systems, models ranging from 500VA up to 15kVA.
2	Cerbo GX for local and remote system monitoring and configuration.
3	GX Touch display gives an instant overview of your system.
4	The Lynx Distributor is a modular DC busbar with locations for four DC fuses and fuse status monitoring.
5	Lynx Smart BMS for 12, 24 or 48V, 500A rating with built-in contactor, battery monitor and GX device communication.
6	BatteryProtect, available in 65, 100 or 220A models, for 12, 24 or 48V, with or without Bluetooth.
7	Solar charger, available up to 100A, for 12, 24 or 48V, with or without Bluetooth.
	Lithium Battery Smart BMS communication cable is attached to the battery. Extension cables are available.
	RJ45 UTP cable, available in lengths ranging from 30 cm to 30m.
	VE Direct cable is available in lengths ranging from 30cm to 10m.
	Do not discharge (orange) signal wire. Remote on/off signal wire (purple)
	AC cable and AC circuit breaker (CB or MCB) and AC earth fault detector (RCD, RCB or GFC).
	Solar panel or solar array.
	A single Lithium Battery Smart or multiples connected in series, creating 12, 24 or 48V.
	DC fuse.
	Positive (red) and negative (black) DC cables. For the correct cable sizing see the Wiring Unlimited book .